



A Level

Data and Formulae v1.0 Jun 2021



$$a^2 + b^2 = c^2$$

SOH CAH TOA

$$A_{\text{sphere}} = 4\pi r^2$$

$$V_{\text{sphere}} = \frac{4}{3}\pi r^3$$

$$c = 3.00 \times 10^8 \text{ m s}^{-1}$$

$$\mu_0 = 4\pi \times 10^{-7} \text{ H m}^{-1}$$

$$\epsilon_0 = 8.85 \times 10^{-12} \text{ F m}^{-1}$$

$$e = 1.60 \times 10^{-19} \text{ C}$$

$$h = 6.63 \times 10^{-34} \text{ J s}$$

$$G = 6.67 \times 10^{-11} \text{ N m}^2 \text{ kg}^{-2}$$

$$N_A = 6.02 \times 10^{23} \text{ mol}^{-1}$$

$$R = 8.31 \text{ J K}^{-1} \text{ mol}^{-1}$$

$$k = 1.38 \times 10^{-23} \text{ J K}^{-1}$$

$$\sigma = 5.67 \times 10^{-8} \text{ W m}^{-2} \text{ K}^{-4}$$

$$\alpha = 2.90 \times 10^{-3} \text{ m K}$$

$$m_e = 9.11 \times 10^{-31} \text{ kg}$$

$$m_p = 1.67(3) \times 10^{-27} \text{ kg}$$

$$m_n = 1.67(5) \times 10^{-27} \text{ kg}$$

$$e/m_e = 1.76 \times 10^{11} \text{ C kg}^{-1}$$

$$e/m_p = 9.58 \times 10^7 \text{ C kg}^{-1}$$

$$g = 9.81 \text{ N kg}^{-1} \text{ or } \text{m s}^{-2}$$

$$u = 1.661 \times 10^{-27} \text{ kg}$$

$$u = 931.5 \text{ MeV}$$

$$m_{\text{Sun}} = 1.99 \times 10^{30} \text{ kg}$$

$$r_{\text{Sun}} = 6.96 \times 10^8 \text{ m}$$

$$m_{\text{Earth}} = 5.97 \times 10^{24} \text{ kg}$$

$$r_{\text{Earth}} = 6.37 \times 10^6 \text{ m}$$

$$E = hf = hc / \lambda$$

$$hf = E_1 - E_2$$

$$hf = \phi + E_{k(\text{max})}$$

$$\lambda = h / p = h / mv$$

$$c = f\lambda$$

$$f = 1 / T$$

$$f = \frac{1}{2l} \sqrt{\frac{T}{\mu}}$$

$$w = \lambda D / s$$

$$d \sin \theta = n\lambda$$

$$n = c / c_s$$

$$n_1 \sin \theta_1 = n_2 \sin \theta_2$$

$$\sin \theta_c = n_2 / n_1 \text{ for } n_1 > n_2$$

$$M = Fd$$

$$a = \Delta v / \Delta t$$

$$v^2 = u^2 + 2as$$

$$s = ut + \frac{1}{2}at^2$$

$$F = ma$$

$$F\Delta t = \Delta(mv)$$

$$E_k = \frac{1}{2}mv^2$$

$$P = \Delta W / \Delta t$$

$$\text{efficiency} = \frac{\text{useful power output}}{\text{power input}}$$

$$\rho = m / V$$

$$F = k\Delta L$$

$$E = \frac{1}{2}F\Delta L$$

$$\text{tensile stress} = F / A$$

$$\text{tensile strain} = \Delta L / L$$

$$\text{Young modulus} = \text{tensile stress} / \text{tensile strain}$$

$$v = \Delta s / \Delta t$$

$$v = u + at$$

$$s = \left(\frac{u+v}{2}\right)t$$

$$F = \Delta(mv) / \Delta t$$

$$W = F s \cos \theta$$

$$\Delta E_p = mg\Delta h$$

$$P = Fv$$

$$I = \Delta Q / \Delta t$$

$$R = V / I$$

$$R_T = R_1 + R_2 + \dots$$

$$\frac{1}{R_T} = \frac{1}{R_1} + \frac{1}{R_2} + \dots$$

$$V = W / Q$$

$$\rho = RA / L$$

$$P = VI = I^2R = V^2 / R$$

$$\epsilon = E / Q$$

$$\epsilon = I(R + r)$$

$$\omega = v / r$$

$$\alpha = v^2 / r = \omega^2 r$$

$$\alpha = -\omega^2 x$$

$$x = A \cos(\omega t)$$

$$T = 2\pi \sqrt{\frac{m}{k}}$$

$$\omega = 2\pi f$$

$$F = mv^2 / r = m\omega^2 r$$

$$v = \pm \omega \sqrt{(A^2 - x^2)}$$

$$v_{\text{max}} = \omega A$$

$$a_{\text{max}} = \omega^2 A$$

$$T = 2\pi \sqrt{\frac{l}{g}}$$

$$Q = mc\Delta\theta$$

$$pV = nRT$$

$$pV = \frac{1}{3}Nm(c_{\text{rms}})^2$$

$$\frac{1}{2}m(c_{\text{rms}})^2 = \frac{3}{2}kT = 3RT / 2N_A$$

$$Q = ml$$

$$pV = NkT$$

$$F = (1/4\pi\epsilon_0)Q_1Q_2 / r^2$$

$$F = EQ$$

$$E = (1/4\pi\epsilon_0)Q / r^2 \quad \Delta W = Q\Delta V$$

$$V = (1/4\pi\epsilon_0)Q / r$$

$$C = Q / V$$

$$E = \frac{1}{2}QV = \frac{1}{2}CV^2 = \frac{1}{2}Q^2 / C$$

$$Q = Q_0(1 - e^{-t/RC}) \quad Q = Q_0 e^{-t/RC}$$

$$\text{time constant} = RC$$

$$F = BIl$$

$$\phi = BA$$

$$I_{\text{rms}} = I_0 / \sqrt{2}$$

$$V_{\text{rms}} = V_0 / \sqrt{2}$$

$$F = BQv$$

$$N\phi = BAN \cos \theta$$

$$\epsilon = N\Delta\phi / \Delta t \quad \epsilon = BAN\omega \sin \omega t$$

$$N_s / N_p = V_s / V_p$$

$$\text{efficiency} = I_s V_s / I_p V_p$$

$$\gamma = 0 \text{ MeV}$$

$$v_e = 0 \text{ MeV}$$

$$v_\mu = 0 \text{ MeV}$$

$$e^\pm = 0.510999 \text{ MeV}$$

$$\mu^\pm = 105.659 \text{ MeV}$$

$$\pi^\pm = 139.576 \text{ MeV}$$

$$\pi^0 = 134.972 \text{ MeV}$$

$$K^\pm = 493.821 \text{ MeV}$$

$$K^0 = 497.762 \text{ MeV}$$

$$p = 938.257 \text{ MeV}$$

$$n = 939.551 \text{ MeV}$$

$$e^-, v_e, \mu^-, v_\mu \quad (L) +1$$

$$e^+, \bar{v}_e, \mu^+, \bar{v}_\mu \quad (L) -1$$

$$u_{\text{quark}} \quad (Q) +2/3e \quad (B) +1/3 \quad (S) 0$$

$$d_{\text{quark}} \quad (Q) -1/3e \quad (B) +1/3 \quad (S) 0$$

$$s_{\text{quark}} \quad (Q) -1/3e \quad (B) +1/3 \quad (S) -1$$

$$I = k / x^2 \quad \Delta N / \Delta t = -\lambda N$$

$$N = N_0 e^{-\lambda t} \quad A = \lambda N$$

$$T_{1/2} = \ln 2 / \lambda \quad R = R_0 A^{1/2}$$

$$E = mc^2$$

$$F = Gm_1m_2 / r^2 \quad g = F / m$$

$$\Delta W = m\Delta V \quad g = GM / r^2$$

$$V = -GM / r \quad g = -\Delta V / \Delta r$$





Options

$$1 \text{ AU} = 1.50 \times 10^{11} \text{ m}$$

$$1 \text{ ly} = 9.46 \times 10^{15} \text{ m}$$

$$1 \text{ pc} = 2.06 \times 10^5 \text{ AU}$$

$$1 \text{ pc} = 3.08 \times 10^{16} \text{ m}$$

$$1 \text{ pc} = 3.26 \text{ ly}$$

$$M = \frac{\text{angle subtended by image at eye}}{\text{angle subtended by object at unaided eye}}$$

$$M = f_o / f_e \quad m - M = 5 \log (d / 10)$$

$$\theta \approx \lambda / D \quad \lambda_{\text{max}} T = 2.9 \times 10^{-3} \text{ mK}$$

$$P = \sigma AT^4$$

$$R_s \approx 2GM / c^2$$

$$\Delta f / f = -\Delta \lambda / \lambda = v / c$$

$$z = -v / c$$

$$v = Hd \quad H = 65 \text{ km s}^{-1} \text{ Mpc}^{-1}$$

$$P = 1 / f$$

$$m = v / u$$

$$1 / f = 1 / u + 1 / v$$

$$I_0 = 1.0 \times 10^{-12} \text{ W m}^{-2}$$

$$\text{intensity level} = 10 \log (I / I_0)$$

$$I = I_0 e^{-\mu x}$$

$$\mu_m = \mu / \rho$$

$$Z = \rho c$$

$$I_r / I_i = (Z_2 - Z_1) / (Z_2 + Z_1)^2$$

$$1 / T_E = 1 / T_B + 1 / T_P$$

$$I = \Sigma mr^2$$

$$E_k = \frac{1}{2} I \omega^2$$

$$\omega_2 = \omega_1 + \alpha t$$

$$\omega_2^2 = \omega_1^2 + 2\alpha\theta$$

$$\theta = \omega_1 t + \frac{1}{2} \alpha t^2$$

$$\theta = \left(\frac{\omega_1 + \omega_2}{2} \right) t$$

$$T = I\alpha$$

$$T = Fr$$

$$L = I\omega$$

$$T\Delta t = \Delta(L\omega)$$

$$W = T\theta$$

$$P = T\omega$$

$$Q = \Delta U + W$$

$$W = p\Delta V$$

$$pV = \text{constant}$$

$$pV = \text{constant}$$

$$\text{efficiency} = \frac{W}{Q_H} = \frac{Q_H - Q_C}{Q_H}$$

$$\text{maximum theoretical efficiency} = \frac{T_H - T_C}{T_H}$$

$$\text{COP}_{\text{ref}} = \frac{Q_C}{W} = \frac{Q_C}{Q_H - Q_C}$$

$$\text{COP}_{\text{hp}} = \frac{Q_H}{W} = \frac{Q_H}{Q_H - Q_C}$$

work done per cycle = area of loop
input power = calorific value x fuel flow rate
indicated power = (area of p-V loop) x (no. of cycles per second) x (no. of cylinders)
friction power = indicated power - brake power

$$F = eV / d$$

$$F = Bev$$

$$r = mv / Be$$

$$\frac{1}{2} mv^2 = eV$$

$$QV / d = mg$$

$$F = 6\pi\eta rv$$

$$c = 1 / \sqrt{\mu_0 \epsilon_0}$$

$$\lambda = h / p = h / \sqrt{2meV}$$

$$t = \frac{t_0}{\sqrt{1 - v^2/c^2}}$$

$$l = l_0 \sqrt{1 - v^2/c^2}$$

$$E = mc^2 = \frac{m_0 c^2}{\sqrt{1 - v^2/c^2}}$$

$$f_0 = \frac{1}{2\pi\sqrt{LC}}$$

$$\text{inverting } \frac{V_{\text{out}}}{V_{\text{in}}} = -\frac{R_f}{R_{\text{in}}}$$

$$\text{summing } V_{\text{out}} = -R_f \left(\frac{V_1}{R_1} + \frac{V_2}{R_2} + \frac{V_3}{R_3} \dots \right)$$

$$\text{bandwidth}_{\text{AM}} = 2f_M$$

$$Q = f_o / f_B$$

$$\text{non-inverting } \frac{V_{\text{out}}}{V_{\text{in}}} = 1 + \frac{R_f}{R_1}$$

$$\text{difference } V_{\text{out}} = (V_+ - V_-) \frac{R_f}{R_1}$$

$$\text{bandwidth}_{\text{FM}} = 2(\Delta f + f_M)$$

$$V_{\text{out}} = A_{\text{OL}} (V_+ - V_-)$$

This data and formulae sheet is for you to use while you're learning A Level Physics and working through practice questions.

Make sure you are also familiar with the official AQA Data and Formulae booklet: especially before you use it for any real exams in the future.

